


## w163 Lampyre t1



## Technical information

<b>Physical</b>	
<b>Material</b>	Opal glass
<b>IP rating</b>	20
<b>Protection class</b>	II

## LED

### Light source

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wästberg Lighting AB apply.

## Article-specific information


<b>Version</b>	t1
<b>Mounting</b>	Base
<b>LED Colour temperature (CCT) / Luminous flux</b>	2700 K / 110 lm
<b>Voltage / System power</b>	220–240 V / Max. 24 W LED
<b>Light control</b>	Dimmer switch on cord
<b>Net weight</b>	1.6 kg
<b>Packaging dimensions</b>	L44 × W38 × H16 cm (0.03 m <sup>3</sup> )
<b>Gross weight</b>	2.5 kg

## Colour

**White (similar to RAL 9010)**

## Art. No. / EAN code

**163T100 / 7330492007564**

**w163 Lampyre t2**

## Article-specific information

<b>Version</b>	t2
<b>Mounting</b>	Base
<b>LED Colour temperature (CCT) / Luminous flux</b>	2700 K / 110 lm
<b>Voltage / System power</b>	220–240 V / Max. 24 W LED
<b>Light control</b>	Dimmer switch on cord
<b>Net weight</b>	4.2 kg
<b>Packaging dimensions</b>	L63 × W58 × H24 cm (0.09 m <sup>3</sup> )
<b>Gross weight</b>	4.5 kg
<b>Colour</b>	<b>Art. No. / EAN code</b>
White (similar to RAL 9010) <input checked="" type="radio"/>	163T200 / 7330492007571