








w241 Faro



Technical information

Physical	
Material	Shade & base: aluminium Internal structure: polycarbonate
Optics	Lens: polycarbonate
IP rating	54
Protection class	III
LED	
Light source	Integrated LED
Lifetime expectancy	L80 / 50,000 h
CRI Colour rendering index	≥ 90
Standard deviation of colour	3-step MacAdam
Replaceable by a professional	
The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wästberg Lighting AB apply.	

Article-specific information

Mounting	
LED Colour temperature (CCT) / Luminous flux	
Voltage / System power	
Light control	
Charging	
Charging socket	
Battery	
Net weight	
Colour	
Grey white (RAL 9002)	
Pure red (RAL 3028)	
Traffic green (RAL 6024)	
Chocolate brown (RAL 8017)	
Black grey (RAL 7012)	
Raw tumbled	
Accessories	
Master dimming device	
Charging adapter	
USB-C cable	
USB-C charger hub (up tp 10 lamps)	

Base
2700 K / 170 lm
110–240 V / 2.5 W
Dimmable
5V, min. 2A (adapter not included)
USB-C (cable not included)
LiFePo4 (included)
1.1 kg

Art. No. / EAN code
241T10227 / 7330492001746
241T10327 / 7330492001753
241T10127 / 7330492001760
241T10727 / 7330492001777
241T10427 / 7330492001784
241T12027 / 7330492001791

Art. No. / EAN code
REMOTE-001 / 7330492002170
CHARGER-001 / 7330492002187
CABLE-001 / 7330492002194
HUB-001 / 7330492002200